

## 4 Pack Polyurethane Nylon Plate - Various Configurations

**Product code: BZWB150LNPB/SETS**

4 pack pressed steel top plate fitted with a red polyurethane on white nylon centred wheel with roller bearings. 150mm wheel diameter, 40mm tread width, 190mm overall height, 135mm x 110mm top plate, 105mm x 80/75mm hole centres with a load capacity of 350kgs per castor / 1050kg per set.



Diameter (mm)	150
Fixing Option	Plate
Castor Type	Fixed, Swivel, Swivel with Total Lock Brake
Height (mm)	190
Bearing Type	Roller
Swivel Radius (mm)	128 Swivel / 145 Braked
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Red Polyurethane on Nylon Rim / 96 Shore A
Fork Thickness (mm)	3
Temperature Resistance	-20 °C TO +70 °C
To Suit Fixing Bolt (mm)	10
Tread (mm)	40
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80
Top Plate Thickness (mm)	4
Configuration	2 x Fixed + 2 x Braked, 2 x Swivel + 2 x Braked, 2 x Swivel + 2 x Fixed
Load Capacity (kg)	1050 Per Set

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

