T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Black Soft Elastic Rubber on Aluminium 55Shore A Stem Swivel Castor Brake 125mm 200kg Load



Product code: BZH125SRERBJSWBST

Pressed steel swivel 16mm threaded castor fitted with a black ergonomic high elastic natural 55 shore A round profile rubber tyre wheel with an aluminium centre with a ball bearing and total lock brake. Wheel diameter 125mm, tread width 40mm, overall height 157mm, top plate 105mm x 86mm, hole centres 80mm x 60mm. Load capacity 200kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC, also available with flat tread details on request

Diameter (mm)	125
Castor Type	Swivel with Total Lock Brake
Fixing Option	Stem
Height (mm)	157
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Ergonomic Rubber on Aluminium Rim / 55 Shore A
Temperature Resistance	-30 ?C TO +80 ?C
Bearing Type	Ball
Load Capacity (kg)	200
Tread (mm)	40
Swivel Radius (mm)	125
Head Dia (mm)	76
To Suit Fixing Bolt (mm)	M16 X 30
Castor Material	Zinc plated