

Black Soft Elastic Rubber on Aluminium Plate Swivel Castor Brake 150mm 270kg Load

Product code: BZK150SRERBJSWB



Fabricated swivel castor with a top plate fixing fitted with a ergonomic black high elastic natural 55 shore A round profile rubber tyred aluminium centred wheel with ball bearings and total lock brake. Wheel diameter 150mm, tread width 47mm, overall height 200mm, top plate 150mm x 110mm, hole centres 105mm x 80mm or 121mm x 59mm. Load capacity 270kg at 4kph and 100kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC

**** FOR INTERNAL AND EXTERNAL TOWING USE ****

Diameter (mm)	150
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	200
Plate Size (mm)	150 x 110
Hole Centres (mm)	105/121 x 80/59
To Suit Fixing Bolt (mm)	12
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	7.5
Fork Thickness (mm)	6
Swivel Radius (mm)	140
Load Capacity (kg)	250
Tread (mm)	47

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

