



## Black Soft Elastic Rubber Plate Swivel Castor Brake 160mm 300kg Load

Product code: BZMM160SRERBJSWB

Pressed steel swivel castor with a top plate fixing fitted with a ergonomic black high elastic natural 55 shore A round profiletyred aluminium centred wheel with a ball journal bearings and total lock brake. Wheel diameter 160mm, tread width 50mm, overall height 195mm, top plate 135mm x 110mm, hole centres 105mm x 80mm. Load capacity 300kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC also available with flat tread details on request



| D' ( ()                  | 400  |
|--------------------------|--|
| Diameter (mm)            | 160  |
| Castor Type              | Swivel with Total Lock Brake                         |
| Fixing Option            | Plate  |
| Height (mm)              | 195  |
| Wheel Material           | Rubber on Aluminium                                  |
| Colour / Shore Hardness  | Black Ergonomic Rubber on Aluminium Rim / 55 Shore A |
| Temperature Resistance   | -30 °C TO +80 °C                                     |
| Bearing Type             | Ball   |
| Load Capacity (kg)       | 300  |
| Tread (mm)               | 50   |
| Swivel Radius (mm)       | 167  |
| Plate Size (mm)          | 135 x 110  |
| Hole Centres (mm)        | 105 x 80   |
| Top Plate Thickness (mm) | 4  |
| Fork Thickness (mm)      | 3  |
| To Suit Fixing Bolt (mm) | 10   |





