

Black Soft Elastic Speed Rubber on Aluminium Plate Swivel Castor 200mm 380kg Load

Product code: BZSPH200SRERBJ

Pressed steel swivel castor with a top plate fixing fitted with a black high elastic natural 55 shore A rubber tyred wheel aluminium centre with ball bearings. Wheel diameter 200mm, tread width 50mm, overall height 238mm, top plate 135mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 380kg at 4kph and 152kph at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC **FOR INTERNAL TOWING ONLY**



Diameter (mm)	200
Castor Type	Swivel
Fixing Option	Plate
Height (mm)	238
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Ergonomic Rubber on Aluminium Rim / 55 Shore A
Temperature Resistance	-30 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	380
Tread (mm)	50
Swivel Radius (mm)	153
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80/75
Top Plate Thickness (mm)	5
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	10

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821 VAT Reg: GB572705729





UKAS

auva

ISO 14001 CERTIFIED