

## Black Soft Elastic Speed Rubber on Aluminium Plate Swivel Castor Brake 200mm 380kg Load

**Product code: BZXP200SRERBJSWBLP**



Pressed steel swivel castor with a flat plate fixing fitted with a black ergonomic high elastic natural 55 shore A round profile rubber tyre on aluminium centred wheel with ball bearings and total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 245mm, plate size 162mm x 140mm, hole centres 140mm x 105mm. Load capacity 380kg at 4kph 152kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC \*\* FOR INTERNAL TOWING ONLY \*\*

Diameter (mm)	200
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	245
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Ergonomic Rubber on Aluminium Rim / 55 Shore A
Temperature Resistance	-30 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	380
Tread (mm)	50
Swivel Radius (mm)	180
Plate Size (mm)	162 X 140
Hole Centres (mm)	140 X 105
Top Plate Thickness (mm)	6
Fork Thickness (mm)	5
To Suit Fixing Bolt (mm)	10

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

