

Black Speed Rubber Swivel Brake Plate Castor 200mm 500kg

Product code: BZSPH200ERBJFPSWB

Pressed steel swivel castor with a top plate fixing fitted with a black high elastic natural 65 shore A rubber tyred wheel aluminium centre with ball bearings and a fixed position brake. Wheel diameter 200mm, tread width 50mm, overall height 252mm, top plate 180mm x 115mm, hole centres 105mm x 80mm. Load capacity 500kg at 4kph and 200kph at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC



| | |
|--------------------------|--|
| Fixing Option | Plate |
| Diameter (mm) | 200 |
| Load Capacity (kg) | 500 |
| Castor Type | Swivel with Fixed Position Total Lock Brake |
| Height (mm) | 252 |
| Wheel Material | Rubber on Aluminium |
| Colour / Shore Hardness | Black Elastic Rubber on Aluminium Rim / 65 Shore A |
| Bearing Type | Ball |
| Tread (mm) | 50 |
| Fork Thickness (mm) | 5 |
| Temperature Resistance | -30 °C TO +80 °C |
| Plate Size (mm) | 180 x 115 |
| Hole Centres (mm) | 105 x 80 |
| Swivel Radius (mm) | 164 |
| Top Plate Thickness (mm) | 19 |
| To Suit Fixing Bolt (mm) | 10 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

