

## Brown Polyurethane Swivel Brake Plate Castor 150mm 500kg

**Product code: BZSPH150PABJFPSWB**

Pressed steel swivel castor with a top plate fixing fitted with a polyurethane tyred aluminium centred wheel with ball bearings and a fixed position total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 204mm, top plate 135mm x 110mm, hole centres 105mm x 80mm. Load capacity 500kg.



|                          |  |
|--------------------------|--|
| Fixing Option            | Plate  |
| Diameter (mm)            | 150  |
| Load Capacity (kg)       | 500  |
| Castor Type              | Swivel with Fixed Position Total Lock Brake      |
| Height (mm)              | 204  |
| Wheel Material           | Polyurethane on Aluminium                        |
| Colour / Shore Hardness  | Brown Polyurethane on Aluminium Rim / 93 Shore A |
| Bearing Type             | Ball   |
| Tread (mm)               | 50   |
| Fork Thickness (mm)      | 5  |
| Temperature Resistance   | -20 °C TO +70 °C                                 |
| Plate Size (mm)          | 180 x 115  |
| Hole Centres (mm)        | 105 x 80   |
| Swivel Radius (mm)       | 164  |
| Top Plate Thickness (mm) | 19   |
| To Suit Fixing Bolt (mm) | 10   |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

