T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Ditherm Plate Swivel Castor Brake 125mm 230kg Load



**Product code: SSMH125AN3SWB**

Grade 304 Stainless steel swivel castor with a top plate fixing fitted with a black Ditherm wheel with palin bore and a total lock brake. Wheel diameter 125mm, tread width 40mm, overall height 158mm, top plate 100mm x 85mm, hole centres 80mm x 60mm or 75mm x 45mm. Load capacity 230kg at a maximum temperature of 280c. REACH compliant, RoHs Compliant, USDA approved FDA approved.

| | |
|---|---|
| Diameter (mm) | 125 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Plate Size (mm) | 100 x 85 |
| Hole Centres (mm) | 80/75 x 60/45 |
| To Suit Fixing Bolt (mm) | 8 |
| Height (mm) | 158 |
| Bearing Type | Plain |
| Swivel Radius (mm) | 125 |
| Wheel Material | Ditherm |
| Colour / Shore Hardness | Black High Temperature Ditherm |
| Temperature Resistance | -40°C to +280°C |
| Load Capacity (kg) | 230 |
| Tread (mm) | 40 |
| Top Plate Thickness (mm) | 2.5 |
| Fork Thickness (mm) | 2.5 |
| Castor Material | Stainless Steel |