

Elastic Rubber Cast Iron Plate Swivel Castor 200mm 1000kg Load

Product code: 2BZK200CUBJ

Twin wheeled swivel castor with a top plate fixing fitted with 2 65 shore A black elastic rubber cast iron centred wheels with ball bearings. Wheel diameter 2 x 200mm, tread width 2 x 50mm, overall height 250mm, top plate 150mm x 110mm, hole centres 105mm x 80mm or 121mm x 59mm. Load capacity 1000kg. - At 6 kph speed, the load of each wheel is advised to be 80% of the load at 4kph - At 10 kph speed, the load of each wheel is advised to be 55% of the load at 4 kph. - At 16 kph speed, the load of each wheel is advised to be 45% of the load at 4kph. - At 20 kph speed, the load of each wheel is advised to be 35% of the load at 4 kph. - No data for elastic rubber wheel over 20 kph.



| | |
|--------------------------|--|
| Diameter (mm) | 200 |
| Fixing Option | Plate |
| Castor Type | Swivel |
| Bearing Type | Ball |
| Plate Size (mm) | 150 x 110 |
| Hole Centres (mm) | 105/121 x 80/59 |
| Height (mm) | 250 |
| Swivel Radius (mm) | 170 |
| To Suit Fixing Bolt (mm) | 12 |
| Wheel Material | Rubber on Cast Iron |
| Colour / Shore Hardness | Black Elastic Rubber on Cast Iron Rim / 65 Shore A |
| Temperature Resistance | "-20 °C TO +60 °C |
| Tread (mm) | 2 x 50 |
| Load Capacity (kg) | 1000 |
| Top Plate Thickness (mm) | 7.5 |
| Fork Thickness (mm) | 6 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

