



## Elastic Rubber Cast Iron Plate Swivel Castor 250mm 1100kg Load

Product code: 2BZQ250CUBJ

Fabricated swivel castor with a flat plate fixing fitted with 2 x black elastic rubber tyred on cast iron centred wheels with ball bearings. Wheel diameter 250mm, tread width 50mm, overall heidht 314mm, plate size 170mm x 140mm, hole centres 140mm x 105mm. Load capacity 1100kg. - At 6 kph speed, the load of each wheel is advised to be 80% of the load at 4kph - At 10 kph speed, the load of each wheel is advised to be 55% of the load at 4 kph. - At 16 kph speed, the load of each wheel is advised to be 45% of the load at 4kph. - At 20 kph speed, the load of each wheel is advised to be 35% of the load at 4 kph. - No data for elastic rubber wheel over 20 kph.



Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
Height (mm)	314
Swivel Radius (mm)	215
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Cast Iron
Colour / Shore Hardness	Black Elastic Rubber on Cast Iron Rim / 65 Shore A
Temperature Resistance	"-20 °C TO +60 °C
Tread (mm)	2 x 50
Load Capacity (kg)	1100
Top Plate Thickness (mm)	12
Fork Thickness (mm)	8





