T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Elastic Rubber Cast Iron Plate Swivel Castor Brake 150mm 700kg Load

Product code: 2BZK150CRBJDBR



Twin wheeled fabricated swivel castor with a top plate fixing fitted with 2 x elastic rubber tyred cast iron wheels with ball bearings and a double wheel brake. Wheel diameter 150mm, tread width 50mm, overall height 200mm, top plate 150mm x 110mm, hole centers 105mm x 80mm or 121mm x 59mm. Load capacity 700kg.

Diameter (mm)	150
Fixing Option	Plate
Castor Type	Swivel with Wheel Brake
Bearing Type	Ball
Plate Size (mm)	150 x 110
Hole Centres (mm)	105/121 x 80/59
Height (mm)	200
Swivel Radius (mm)	160
To Suit Fixing Bolt (mm)	12
Wheel Material	Rubber on Cast Iron
Colour / Shore Hardness	Black Elastic Rubber on Cast Iron Rim / 75 Shore A
Temperature Resistance	"-20 ?C TO +60 ?C
Tread (mm)	2 x 60
Load Capacity (kg)	700
Top Plate Thickness (mm)	7.5
Fork Thickness (mm)	6
Castor Material	Zinc plated