

Elastic Rubber Cast Iron Plate Swivel Castor Brake 200mm 500kg Load

Product code: BZQ200CUBJSWB/50



Fabricated swivel castor with a flat plate fixing fitted with a 65 shore A black elastic rubber tyred cast iron centred wheel with ball bearings and total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 264mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 500kg at 4kph and 175kg at 20kph. ** FOR INTERNAL AND EXTERNAL TOWING USE**

Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	264
Plate Size (mm)	170 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Cast Iron
Colour / Shore Hardness	Black Elastic Rubber on Cast Iron Rim / 65 Shore A
Temperature Resistance	-20 °C TO +60 °C
Top Plate Thickness (mm)	12
Fork Thickness (mm)	10
Swivel Radius (mm)	167
Load Capacity (kg)	500
Tread (mm)	50

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

