

## Elastic Rubber Cast Iron Plate Swivel Castor Brake Locking Castor 200mm 450kg Load

**Product code: JAZHS200CRBJSWB**

Side winding jacking unit fitted with a fabricated swivel castor with a 200mm black elastic rubber tyred cast iron centred wheel with ball bearings and wheel brake, wheel to carry a maximum load capacity of 450kg per complete unit. Please note Jacking castors are rated on a different principle to other castors. They lift the load off the floor and therefore each castor is liable to carry half the total load, also please note the maximum lift is 200mm but when jacked up to the height please be aware of any obstacles as a sudden shock could result in the inner square tube bend around the outer tube. PLEASE NOTE: BIL do not recommend brakes on jacking castors. DO NOT OVERWIND Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 200  |
| Castor Height (mm)       | 241  |
| Castor Type              | Swivel with Total Lock Brake                       |
| Swivel Radius (mm)       | 156  |
| Fixing Option            | Plate  |
| Bearing Type             | Ball   |
| To Suit Fixing Bolt (mm) | 10   |
| Wheel Material           | Rubber on Cast Iron                                |
| Colour / Shore Hardness  | Black Elastic Rubber on Cast Iron Rim / 75 Shore A |
| Temperature Resistance   | -20 °C TO +60 °C                                   |
| Load Capacity (kg)       | 450  |
| Tread (mm)               | 50   |
| Height (mm)              | 648 / 848  |
| Lifting Stroke (mm)      | 200  |
| Handle Option            | Fixed  |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

