
T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Elastic Rubber on Aluminium Plate Fixed Castor 160mm 300kg Load



Product code: BZKFL160ERBJSPR

Fabricated fixed castor with top plate fixing fitted with a 160mm x 50mm black high elastic natural 65 shore A rubber tyred aluminium centred wheel with ball bearings overall height 188mm/208mm, plate size 138mm x 110mm, hole centres 105mm x 80mm. fitted with a 600kg red polyurethane spring but load capacity is 400kg at 4kph and 140kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC

Diameter (mm)	160
Fixing Option	Plate
Castor Type	Fixed
Bearing Type	Ball
Height (mm)	208
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80/75
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30°C to +80°C
Top Plate Thickness (mm)	6
Fork Thickness (mm)	6
Load Capacity (kg)	400
Tread (mm)	50
Castor Material	Zinc plated