

## Elastic Rubber on Aluminium Plate Swivel Castor 125mm 250kg Load

**Product code: BZEH125ERBJLP**

Pressed steel swivel castor with a top plate fixing fitted with a 65 shore A black elastic rubber on aluminium centred wheel with ball bearing . Wheel diameter 125mm, tread width 40mm, overall height 156mm, top plate 135mm x 110mm, hole centres 105mm x 80mm or 116mm x 63.5mm Load capacity 250kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC



Diameter (mm)	125
Castor Type	Swivel
Fixing Option	Plate
Height (mm)	156
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	250
Tread (mm)	40
Swivel Radius (mm)	106
Plate Size (mm)	135 x 110
Hole Centres (mm)	105/116 x 80/64
Top Plate Thickness (mm)	3
Fork Thickness (mm)	3
To Suit Fixing Bolt (mm)	10

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

