

## Elastic Rubber on Aluminium Plate Swivel Castor 125mm 250kg Load

**Product code: JAZ125ERBJ**

Zinc plated box jacking unit with side fitting plate and a 75mm lift fitted with a 125mm black elastic rubber tyre on aluminium centred wheel with ball bearings with a load capacity of 200kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. 1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. Please refer to the BIL catalogue or request a drawing. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC



Diameter (mm)	125
Castor Height (mm)	157
Castor Type	Swivel
Swivel Radius (mm)	104
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Load Capacity (kg)	250
Tread (mm)	40
Height (mm)	395 / 470
Lifting Stroke (mm)	75

## BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

