

## Elastic Rubber on Aluminium Plate Swivel Castor 250mm 1300kg Load

**Product code: 2BZQ250ERBJ**



Fabricated swivel castor with a flat plate fixing fitted with 2 x black high elastic natural 65 shore A rubber tyred on aluminium centred wheels with ball bearings. Wheel diameter 250mm, tread width 2 x 50mm, overall height 314mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 1300kg at 4kph and 520kg at 10kph. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC \*\* FOR INTERNAL AND EXTERNAL TOWING USE \*\*

Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
Height (mm)	314
Swivel Radius (mm)	215
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	&quot;-30 °C TO +80 °C
Tread (mm)	2 x 50
Load Capacity (kg)	1300
Top Plate Thickness (mm)	12
Fork Thickness (mm)	8

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

