

Elastic Rubber on Aluminium Plate Swivel Castor Brake 100mm 200kg Load

Product code: BZEH100ERBJSWBLP

Pressed steel swivel castor with a top plate fixing fitted with a black 65 shore A elastic rubber tyre on a black nylon centre with a ball bearing and total lock brake. Wheel diameter 100mm, tread width 40mm, overall height 128mm, top plate 135mm x 100mm, hole centres 105mm x 80mm or 116mm x 63.5mm Load capacity 200kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC



Diameter (mm)	100
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	128
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	200
Tread (mm)	40
Swivel Radius (mm)	115
Plate Size (mm)	135 x 110
Hole Centres (mm)	105/116 x 80/64
Top Plate Thickness (mm)	3
Fork Thickness (mm)	3
To Suit Fixing Bolt (mm)	10

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821 VAT Reg: GB572705729





UKAS

auva

ISO 14001 CERTIFIED