

Elastic Rubber on Aluminium Plate Swivel Castor Brake Footguard 125mm 250kg load

Product code: BZH125ERBJSWBFG

Pressed steel swivel castor with a top plate fixing with a black elastic rubber tyre wheel with an aluminium centre with ball bearings, total lock brake and footguard. Wheel diameter 125mm, tread width 40mm, overall height 155mm, top plate 105mm x 86mm, hole centres 80mm x 60mm. Load capacity 250kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC



Height (mm)	155
Tread (mm)	40
To Suit Fixing Bolt (mm)	8
Bearing Type	Ball
Diameter (mm)	125
Wheel Material	Rubber on Aluminium
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Load Capacity (kg)	250
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Swivel Radius (mm)	125
Plate Size (mm)	105 x 86
Hole Centres (mm)	80 X 60
Fork Thickness (mm)	4
Top Plate Thickness (mm)	4
Temperature Resistance	-30 °C TO +80 °C

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

