



Elastic Rubber on Aluminium Plate Swivel Castor Brake Locking Castor 100mm 200kg Load

Product code: JAZ100ERBJSWB

Zinc plated box jacking unit with side fitting plate and a 75mm lift fitted with a 100mm black elastic rubber tyre on aluminium centred wheel with ball bearings and a total lock brake with a load capacity of 160kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units.1 extra safety point is when jacked up please beware of any obstacles as a sudden shock or leaving the brake on could result in the inner square tube bending around the outer tube. Please refer to the BIL catalogue or request a drawing. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC



Diameter (mm)	100
Castor Height (mm)	128
Castor Type	Swivel with Total Lock Brake
Swivel Radius (mm)	120
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Aluminium
Colour / Shore Hardness	Black Elastic Rubber on Aluminium Rim / 65 Shore A
Temperature Resistance	-30 °C TO +80 °C
Load Capacity (kg)	200
Tread (mm)	40
Height (mm)	366 / 441
Lifting Stroke (mm)	75





