

Elastic Speed Rubber Fixed Plate Castor 406mm 1900kg Load

Product code: 2BZSABF400MKCUBJ



POA Fabricated zinc plated twin wheel swivel castor with fixed plate fixing fitted with 2x black elastic rubber tyred on a steel disc centred wheel with ball bearings. Wheel diameter 406mm, tread width 2 x 104mm, overall height 484mm, plate size 175mm x 140mm, hole centre's 140mm x 105mm. Load capacity 1900kg at 4kph, 1040kg at 10kph and 860kg at 16kph
****MANUFACTURED TO ORDER****

Diameter (mm)	400
Fixing Option	Plate
Castor Type	Fixed
Bearing Type	Ball
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
Height (mm)	484
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Steel
Colour / Shore Hardness	Black Elastic Rubber on Steel Rim / 65 Shore A
Temperature Resistance	"-20 °C TO +60 °C
Tread (mm)	2 x 104
Load Capacity (kg)	1900

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

