

Elastic Speed Rubber Plate Swivel Brake Castor 250mm 900kg Load

Product code: 2BZSAB250MKCUBJDBR



POA Fabricated zinc plated twin wheel swivel braked castor with plate fixing fitted 2x black elastic rubber tyred on a steel disc centred wheel with ball bearings. Wheel diameter 250mm, tread width 2 x 84mm, overall height 310mm, plate size 135mm x 110mm, hole centre's 105mm x 80mm. Load capacity 900kg at 4kph, 500kg at 10kph and 400kg at 16kph
****MANUFACTURED TO ORDER****

| | |
|--------------------------|--|
| Diameter (mm) | 250 |
| Fixing Option | Plate |
| Castor Type | Swivel with Wheel Brake |
| Bearing Type | Ball |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80 |
| Height (mm) | 310 |
| Swivel Radius (mm) | 200 |
| To Suit Fixing Bolt (mm) | 10 |
| Wheel Material | Rubber on Steel |
| Colour / Shore Hardness | Black Elastic Rubber on Steel Rim / 65 Shore A |
| Temperature Resistance | "-20 °C TO +60 °C |
| Tread (mm) | 2 x 84 |
| Load Capacity (kg) | 900 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

