

Elastic Speed Rubber Plate Swivel Braked Castor 406mm 1900kg Load

Product code: 2BZSAB400MKCUBJDBR

POA Fabricated zinc plated twin wheel swivel braked castor with plate fixing fitted with 2x black elastic rubber tyred on a steel disc centred wheel with ball bearings. Wheel diameter 406mm, tread width 2 x 104mm, overall height 484mm, plate size 175mm x 140mm, hole centre's 140mm x 105mm. Load capacity 1900kg at 4kph, 1040kg at 10kph and 860kg at 16kph **MANUFACTURED TO ORDER**



Diameter (mm)	400
Fixing Option	Plate
Castor Type	Swivel with Wheel Brake
Bearing Type	Ball
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
Height (mm)	484
Swivel Radius (mm)	278
To Suit Fixing Bolt (mm)	14
Wheel Material	Rubber on Steel
Colour / Shore Hardness	Black Elastic Rubber on Steel Rim / 65 Shore A
Temperature Resistance	"-20 °C TO +60 °C
Tread (mm)	2 x 104
Load Capacity (kg)	1900

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821 VAT Reg: GB572705729





UKAS

auva

ISO 14001 CERTIFIED