T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Elastic Speed Rubber Plate Swivel Castor 250mm 450kg Load



Product code: BZSAB250MKCUBJ

Fabricated zinc plated swivel castor with plate fixing fitted with a black elastic rubber tyred on a steel disc centered wheel with ball bearings. Wheel diameter 250mm, tread width 84mm, overall height 305mm, plate size 175mm x 140mm, hole center's 140mm x 105mm. Load capacity 450kg at 4kph, 250kg at 10kph and 200kg at 16kph ** FOR INTERNAL AND EXTERNAL TOWING USE **

Diameter (mm)	250
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	305
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Steel
Colour / Shore Hardness	Black Elastic Rubber on Steel Rim / 65 Shore A
Temperature Resistance	-20°C to +60°C
Top Plate Thickness (mm)	8
Fork Thickness (mm)	6
Swivel Radius (mm)	200
Load Capacity (kg)	450
Tread (mm)	84
Castor Material	Zinc plated