

Elastic Speed Rubber Plate Swivel Castor 406mm 950kg Load

Product code: BZSAB400MKCUBJ

Fabricated zinc plated swivel castor with plate fixing fitted with a black elastic rubber tyred on a steel disc centred wheel with ball bearings. Wheel diameter 400mm, tread width 104mm, overall height mm, plate size 175mm x 140mm, hole centers 140mm x 105mm. Load capacity 950kg at 4kph, 520kg at 10kph and 430kg at 16kph ** FOR INTERNAL AND EXTERNAL TOWING USE **



Diameter (mm)	400
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	476
Plate Size (mm)	175 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Steel
Colour / Shore Hardness	Black Elastic Rubber on Steel Rim / 65 Shore A
Temperature Resistance	-20 °C TO +60 °C
Top Plate Thickness (mm)	8
Fork Thickness (mm)	6
Swivel Radius (mm)	303
Load Capacity (kg)	950
Tread (mm)	114

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

