T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Electrically Conductive Polyurethane Nylon Swivel Castor Bolthole 125mm 150kg



**Product code: SSMM125PNBECBH12**

Grade 304 Pressed stainless steel swivel castor with a 12mm bolt hole fitted with a black electrically conductive polyurethane on nylon wheel with roller bearing. Wheel diameter 125mm, tread width 35mm, overall height 155mm,. Load capacity 150kg Conductive ffers a resistance R<10000 Ohm.

| | |
|---|---|
| Diameter (mm) | 125 |
| Fixing Option | Bolt Hole |
| Castor Type | Swivel |
| Height (mm) | 155 |
| Wheel Material | Polyurethane on Nylon |
| Colour / Shore Hardness | Black Polyurethane on Nylon Rim / 97 Shore A |
| Bearing Type | Roller |
| Tread (mm) | 35 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 12 |
| Load Capacity (kg) | 150 |
| Temperature Resistance | -20°C to +80°C |
| Head Dia (mm) | 76 |
| Swivel Radius (mm) | 95 |
| Castor Material | Stainless Steel |