

## Electrically Conductive Polyurethane Nylon Swivel Castor Brake Bolthole 100mm 110kg

**Product code: SSMM100PNBECBH12SWB**

Grade 304 Pressed stainless steel swivel castor with bolt hole fixing fitted with a black electrically conductive polyurethane tyre nylon centred wheel with stainless steel roller bearings and swivel wheel brake. Wheel diameter 100mm, tread width 30mm, overall height 128mm, 12mm bolt hole. Load capacity 110kg. Conductive offers a resistance  $R < 10000 \text{ Ohm}$



Diameter (mm)	100
Fixing Option	Bolt Hole
Castor Type	Swivel with Total Lock Brake
Height (mm)	128
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Black Polyurethane on Nylon Rim / 97 Shore A
Bearing Type	Roller
Tread (mm)	30
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	12
Load Capacity (kg)	120
Temperature Resistance	-20 °C TO +80 °C
Head Dia (mm)	76
Swivel Radius (mm)	118

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

