T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Electrically Conductive Polyurethane Nylon Swivel Castor Brake Plate 125mm 150kg



Product code: SSMM125PNBECSWB

Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a black electrically conductive polyurethane on nylon wheel with roller bearing and a total lock brake. Wheel diameter 125mm, tread width 35mm, overall height 155mm, top plate 105mm x 85mm, hole centres 80mm x 60mm. Load capacity 150kg Conductive ffers a resistance R<10000 Ohm.

Diameter (mm)	125
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Height (mm)	155
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Black Polyurethane on Nylon Rim / 97 Shore A
Bearing Type	Roller
Tread (mm)	35
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	8
Load Capacity (kg)	150
Temperature Resistance	-20°C to +80°C
Plate Size (mm)	105 X 85
Hole Centres (mm)	80 X 60
Top Plate Thickness (mm)	2
Swivel Radius (mm)	123
Castor Material	Stainless Steel