T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Electrically Conductive Polyurethane Nylon Swivel Castor Brake Plate 200mm 390kg



Product code: SSMM200PNBECSWB

Grade 304 Pressed stainless steel swivel castor with a top plate fitted with a black electrically conductive polyurethane tyre on black nylon centred wheel with roller bearings and a total lock brake, 200mm wheel diameter, 50mm tread width, 235mm overall height, 135mm x 110mm top plate, 105 x 80mm bolt holes, with a load capacity of 390kgs. Conductive offers a resistance R<10000 Ohm

Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Height (mm)	235
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Black Polyurethane on Nylon Rim / 97 Shore A
Bearing Type	Roller
Tread (mm)	50
Fork Thickness (mm)	3
To Suit Fixing Bolt (mm)	10
Load Capacity (kg)	400
Temperature Resistance	-20 ?C TO +80 ?C
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80
Top Plate Thickness (mm)	3
Swivel Radius (mm)	167
Castor Material	Stainless Steel