

Electrically Conductive Polyurethane Nylon Swivel Castor Plate 200mm 390kg

Product code: SSMM200PNBEC



Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with a black electrically conductive polyurethane on nylon wheel with roller bearings. Wheel diameter 200mm, tread width 50mm, overall height 235mm, top plate 135mm x 110mm, hole centres 105 x 80mm. Load capacity 400kg Conductive offers a resistance $R < 10000 \text{ Ohm}$

Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel
Height (mm)	235
Wheel Material	Polyurethane on Nylon
Colour / Shore Hardness	Black Polyurethane on Nylon Rim / 97 Shore A
Bearing Type	Roller
Tread (mm)	50
Fork Thickness (mm)	3
To Suit Fixing Bolt (mm)	10
Load Capacity (kg)	400
Temperature Resistance	-20 °C TO +80 °C
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80
Top Plate Thickness (mm)	3
Swivel Radius (mm)	153

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

