

Electrically Conductive Rubber Bolt Hole Fixed Castor 75mm 60kg Load

Product code: SSRAF75GRECBJBH10

Grade 304 Pressed stainless steel fixed castor with a 10mm bolt hole fitted with a grey electrically conductive rubber tyre on polypropylene centred wheel with ball bearing. Wheel diameter 75mm, tread width 24mm, overall height 101mm. plate size 60mm x 60mm, hole centres 49.5mm x 49.5mm or 42.5mm x 42.5mm Load capacity 60kg. Conductive offers a resistance R<10__ ****MANUFACTURED TO ORDER****



| | |
|--------------------------|---|
| Diameter (mm) | 75 |
| Fixing Option | Bolt Hole |
| Castor Type | Fixed |
| Height (mm) | 101 |
| Wheel Material | Rubber on Polypropylene |
| Colour / Shore Hardness | Grey Rubber on Polypropylene Rim / 85 Shore A |
| Bearing Type | Ball |
| Tread (mm) | 24 |
| Fork Thickness (mm) | 1.8 |
| To Suit Fixing Bolt (mm) | 10 |
| Load Capacity (kg) | 60 |
| Temperature Resistance | -15 °C TO +80 °C |
| Head Dia (mm) | 50 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

