

Electrically Conductive Rubber Bolt Hole Fixed Castor 75mm 70kg Load

Product code: SSMF75GRECBJBH12

Stainless steel fixed castor with a 12mm bolt hole fitted with a grey electrically conductive tyre on a black polypropylene centred wheel with ball bearing. Wheel diameter 75mm, tread width 32mm, overall height 109mm, top plate 90mm x 70mm, hole centres 75mm x 56mm or 64mm x 44mm. Load capacity 70kg. Conductive offers a resistance $R < 10 \Omega$

****MANUFACTURED TO ORDER****



| | |
|--------------------------|---|
| Diameter (mm) | 75 |
| Fixing Option | Bolt Hole |
| Castor Type | Fixed |
| Height (mm) | 109 |
| Wheel Material | Rubber on Polypropylene |
| Colour / Shore Hardness | Grey Rubber on Polypropylene Rim / 85 Shore A |
| Bearing Type | Ball |
| Tread (mm) | 32 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 12 |
| Load Capacity (kg) | 90 |
| Temperature Resistance | -15 °C TO +80 °C |
| Head Dia (mm) | 60 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

