

## Electrically Conductive Rubber Bolt Hole Swivel Castor 100mm 70kg Load

**Product code: SSRA100GRECBH10**

Grade 304 Pressed stainless steel swivel castor with a 10mm bolt hole fitted with a grey electrically conductive rubber tyre on polypropylene centred wheel with a plain bore. Wheel diameter 100mm, tread width 24mm, overall height 124mm. load capacity 70kg. Conductive offers a resistance  $R < 10 \Omega$



|                          |   |
|--------------------------|---|
| Diameter (mm)            | 100   |
| Fixing Option            | Bolt Hole                                     |
| Castor Type              | Swivel  |
| Height (mm)              | 124   |
| Wheel Material           | Rubber on Polypropylene                       |
| Colour / Shore Hardness  | Grey Rubber on Polypropylene Rim / 85 Shore A |
| Bearing Type             | Plain   |
| Tread (mm)               | 24  |
| Fork Thickness (mm)      | 1.8   |
| To Suit Fixing Bolt (mm) | 10  |
| Load Capacity (kg)       | 70  |
| Temperature Resistance   | -15 °C TO +80 °C                              |
| Head Dia (mm)            | 50  |
| Swivel Radius (mm)       | 90  |

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

