

## Electrically Conductive Rubber Bolt Hole Swivel Castor Brake 125mm 200kg

**Product code: SSMM125RNBJECSBH12SWB**



Grade 304 Stainless steel swivel castor with a bolt hole fixing fitted with a 65 shore A black elastic electrically conductive rubber wheel on a black nylon centre with ball bearings (Not stainless steel) with total lock brake. Wheel diameter 125mm, tread width 36mm, overall height 155mm, bolt hole 12mm. Load capacity 200Kg. Conductivity range is  $10^3$  ohm to  $10^4$  ohm

Diameter (mm)	125
Fixing Option	Bolt Hole
Castor Type	Swivel with Total Lock Brake
Height (mm)	155
Wheel Material	Rubber on Nylon
Colour / Shore Hardness	Black Elastic Rubber on Nylon Rim / 65 Shore A
Bearing Type	Ball
Tread (mm)	36
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	12
Load Capacity (kg)	200
Temperature Resistance	-20 °C TO +60 °C
Head Dia (mm)	76
Swivel Radius (mm)	123

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

