T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Electrically Conductive Rubber Plate Fixed Castor 125mm 80kg Load



Product code: SSRAF125GRECBJ

Grade 304 Pressed stainless steel fixed castor with a flate plate fitted with a grey electrically conductive rubber tyre on polypropylene centred wheel with ball bearings. Wheel diameter 125mm, tread width 24mm, overall height 149mm. plate size 60mm x 60mm, hole centres 49.5mm x 49.5mm or 42.5m,m x 42.5mm Load capacity 80kg.Conductive offers a resistance R<10__

MANUFACTURED TO ORDER

Diameter (mm)	125
Fixing Option	Plate
Castor Type	Fixed
Height (mm)	149
Wheel Material	Rubber on Polypropylene
Colour / Shore Hardness	Grey Rubber on Polypropylene Rim / 85 Shore A
Bearing Type	Ball
Tread (mm)	24
Fork Thickness (mm)	1.8
To Suit Fixing Bolt (mm)	6
Load Capacity (kg)	80
Temperature Resistance	-15°C to +80°C
Plate Size (mm)	60 x 60
Hole Centres (mm)	49/43 x 49/43
Top Plate Thickness (mm)	1.8
Castor Material	Stainless Steel

BIL GROUP LTD
Porte Marsh Road, Calne, Wiltshire, SN11 9BW
Registered in England No: 2603821
VAT Reg: GB572705729