T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Electrically Conductive Rubber Plate Fixed Castor 150mm 100kg Load



Product code: SSMF150GREC

Grade 304 Stainless steel fixed castor with a top plate fixing fitted with a grey elecctrically conductive tyre on a black polypropylene centred wheel with plain bore. Wheel diameter 150mm, tread width 32mm, overall height 181mm, top plate 90mm x 70mm, hole centres 75mm x 56m or 64mm x 44mm. Load capacity 100kg.Conductive offers a resistance R<10__
MANUFACTURED TO ORDER

Diameter (mm)	150
Fixing Option	Plate
Castor Type	Fixed
Height (mm)	181
Wheel Material	Rubber on Polypropylene
Colour / Shore Hardness	Grey Rubber on Polypropylene Rim / 85 Shore A
Bearing Type	Plain
Tread (mm)	32
Fork Thickness (mm)	2
To Suit Fixing Bolt (mm)	8
Load Capacity (kg)	100
Temperature Resistance	-15°C to +80°C
Plate Size (mm)	90 x 70
Hole Centres (mm)	75/64 x 56/44
Top Plate Thickness (mm)	2
Castor Material	Stainless Steel