T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Electrically Conductive Rubber Plate Fixed Castor 150mm 100kg Load



Product code: BZMF150GREC

Pressed steel fixed castor with a top plate fitted with a grey electrically conductive rubber on grey polypropylene centred wheel with a plain bore,Wheel diameter 150mm, 32mm tread width, 181mm overall height, 90mm x 70mm top plate, 75mm x 56mm or 64mm x 44mm bolt holes, with a load capacity of 100kgs. Conductive offers a resistance R<10__
MANUFACTURED TO ORDER

Diameter (mm)	150
Fixing Option	Plate
Castor Type	Fixed
Plate Size (mm)	90 x 70
Hole Centres (mm)	64/75 x 44/56
Height (mm)	181
Bearing Type	Plain
Wheel Material	Electrically Conductive Rubber
Colour / Shore Hardness	Grey Electrically Conductive Rubber on Nylon Rim / 85 Shore A
Top Plate Thickness (mm)	2
Fork Thickness (mm)	2
Temperature Resistance	-15°C to +80°C
To Suit Fixing Bolt (mm)	8
Tread (mm)	32
Load Capacity (kg)	100
Castor Material	Zinc plated