

Electrically Conductive Rubber Plate Swivel Castor Brake 200mm 350kg

Product code: SSMM200RNBJECSWB

Grade 304 Stainless steel swivel castor with a top plate fixing fitted with a 65 shore A black elastic electrically conductive rubber wheel on a black nylon centre with ball bearings and a total lock brake. Wheel diameter 200mm, tread width 50mm, overall height 235mm, top plate 135mm x 110mm, hole centres 105mm x 80mm Load capacity 350kg. Conductivity range is 10^3 ohm to 10^4 ohm



| | |
|--------------------------|--|
| Diameter (mm) | 200 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Height (mm) | 235 |
| Wheel Material | Rubber on Nylon |
| Colour / Shore Hardness | Black Elastic Rubber on Nylon Rim / 65 Shore A |
| Bearing Type | Ball |
| Tread (mm) | 50 |
| Fork Thickness (mm) | 3 |
| To Suit Fixing Bolt (mm) | 10 |
| Load Capacity (kg) | 400 |
| Temperature Resistance | -20 °C TO +60 °C |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80 |
| Top Plate Thickness (mm) | 3 |
| Swivel Radius (mm) | 167 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

