
T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Ergonomic Polyurethane Plate Swivel Castor 200mm 1500kg Load



Product code: 2BZK200RPTABJ

Twin wheel fabricated swivel castor with a top plate fixing fitted with 2 brown ergonomic polyurethane tyred aluminium centred wheel with a ball bearing. Wheel diameter 200mm, tread width 50mm, overall height 250mm, plate size 150mm x 110mm, hole centres 105mm x 80mm or 121mm x 59mm. Load capacity 1500kg.

Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Plate Size (mm)	150 x 110
Hole Centres (mm)	105/121 x 80/59
Height (mm)	250
Swivel Radius (mm)	165
To Suit Fixing Bolt (mm)	12
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Ergonomic Polyurethane on Aluminium Rim / 95 Shore A
Temperature Resistance	"-20 ?C TO +80 ?C
Tread (mm)	2 x 50
Load Capacity (kg)	1500
Top Plate Thickness (mm)	8
Fork Thickness (mm)	6