

## Ergonomic Polyurethane Plate Swivel Castor 200mm 600kg Load

**Product code: BZMJ200RPTABJ**

Fabricated white zinc ROHS plated swivel castor with a flat plate fixing fitted with a round profile polyurethane on aluminium centred wheel with ball bearings, Wheel diameter 200mm, tread width 50mm, overall height 240mm, plate size 138mm x 110mm, hole centres 105mm x 80mm/75mm. Load capacity 600kg.



Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	241
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80/75
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Brown Ergonomic Polyurethane on Aluminium Rim / 95 Shore A
Temperature Resistance	-20 °C TO +80 °C
Top Plate Thickness (mm)	7
Fork Thickness (mm)	6
Swivel Radius (mm)	156
Load Capacity (kg)	600
Tread (mm)	50

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

