T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Ergonomic Polyurethane Plate Swivel Castor Brake 150mm 575kg Load

Product code: BZSAB150RPTABJSWB



Fabricated yellow ROHS zinc plated swivel castor with plate fixing fitted with a brown 95 shore A polyurethane tyre aluminium centred wheel centred wheel with ball bearings and a total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 200mm, plate size 138mm x 110mm, hole centrtes 105mm x 80mm/75mm. Load capacity 575kg

Diameter (mm)	150
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	200
Plate Size (mm)	138 x 110
Hole Centres (mm)	105 x 80
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Brown Ergonomic Polyurethane on Aluminium Rim / 95 Shore A
Temperature Resistance	-20 ?C TO +80 ?C
Top Plate Thickness (mm)	8
Fork Thickness (mm)	6
Swivel Radius (mm)	145
Load Capacity (kg)	575
Tread (mm)	50
Castor Material	Zinc plated