T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

# Grey Soft Elastic Rubber Plate Swivel Castor Brake 160mm 300kg Load



**Product code: SSMM160SRERGBJSWB**

Grade 304 Pressed stainless steel swivel castor with a top plate fixing fitted with an ergonomic grey high elastic natural 55 shore A round profile rubber tyred aluminium centred wheel with stainless steel ball bearings and a total lock brake. Wheel diameter 160mm, tread width 50mm, overall height 195mm, top plate 140mm x 110mm, hole centres 105mm x 80mm. Load capacity 300kg. REACH compliant also PAH-Free rubber to confirm to EU-directive 2005/69/EC, also available with flat tread details on request

| | |
|---|---|
| Diameter (mm) | 160 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Height (mm) | 195 |
| Wheel Material | Rubber on Aluminium |
| Colour / Shore Hardness | Grey Ergonomic Rubber on Aluminium Rim / 55 Shore A |
| Bearing Type | Ball |
| Tread (mm) | 50 |
| Fork Thickness (mm) | 2 |
| To Suit Fixing Bolt (mm) | 10 |
| Load Capacity (kg) | 300 |
| Temperature Resistance | -30°C to +80°C |
| Plate Size (mm) | 135 x 110 |
| Hole Centres (mm) | 105 x 80 |
| Top Plate Thickness (mm) | 3 |
| Swivel Radius (mm) | 167 |
| Castor Material | Stainless Steel |