

Pneumatic 400mm Roller Bearing Wheel 300kg Load

Product code: BZWPMR400254R



Black pneumatic tyred grey steel disc centred wheel with a roller bearing bore (sorry no grease nipple). Fitted with a 4 ply ribbed tread patterned tyre. Wheel diameter 400mm, tread width 100mm, hub 75mm, bore 25mm. Load capacity 300kg for non-towing applications. REACH Compliant. Please note we manufacture to order and therefore a 24 hour delivery may not be possible Maximum SWL are quoted according to speed: higher speed will reduce SWL. Load capacities recorded on tyre walls represent manufacturers recommended maximum load at 10 KPH, whilst higher SWL figures stated within our catalogue are based upon 4kph maximum speeds. Refer to our catalogue for SWL if the wheel is never to be used at over 4kph rather than the figure recorded on the tyre. Always check the intended application and base the required SWL capacity according to speed rating. If you have any doubts then please contact BIL before using these wheels. Please note these wheels are not suitable for foam filling as standard. Please ask about an upgrade using our Butyl inner tubes to suit this purpose or otherwise consider our puncture proof range of wheels.

| | |
|-------------------------|--|
| Load Capacity (kg) | 300 |
| Wheel Material | Pneumatic tyre on Pressed Steel |
| Diameter (mm) | 400 |
| Bearing Type | Roller |
| Hub Width (mm) | 75 |
| Bore Size (mm) | 25 |
| Tread (mm) | 100 |
| Colour / Shore Hardness | Black Pneumatic Tyre on Steel Rims / 4 Ply |
| Temperature Resistance | -10 °C TO +60 °C |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

