

Pneumatic 400mm Roller Bearing Wheel 300kg Load

Product code: BZWPMR40020754R/RED



Black pneumatic tyred red steel disc centred wheel with a roller bearing bore (sorry no grease nipple). Fitted with a 4 ply ribbed tread patterned tyre. Wheel diameter 400mm, tread width 100mm, hub 75mm, bore 20mm. Load capacity 300kg for non-towing applications please note we manufacture to order and therefore a 24 hour delivery may not be possible. Please note these wheels are not suitable for foam filling as standard. Please ask about an upgrade using our Butyl inner tubes to suit this purpose or otherwise consider our puncture proof range of wheels.

| | |
|-------------------------|--------------------------------------------|
| Wheel Material | Pneumatic tyre on Pressed Steel |
| Diameter (mm) | 400 |
| Load Capacity (kg) | 300 |
| Bearing Type | Roller |
| Bore Size (mm) | 20 |
| Tread (mm) | 100 |
| Hub Width (mm) | 75 |
| Colour / Shore Hardness | Black Pneumatic Tyre on Steel Rims / 4 Ply |
| Temperature Resistance | -10 °C TO +60 °C |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

