

Pneumatic 400mm Roller Bearing Wheel 350kg Load

Product code: BZWPMR40020656D

Black pneumatic tyred red steel disc centred wheel with a roller bearing bore (sorry no grease nipple). Fitted with a 6 ply diamond tread patterned tyre. Wheel diameter 400mm, tread width 100mm, hub 65mm, bore 20mm. Load capacity 350kg for non-towing applications. REACH Compliant. Please note we manufacture to order and therefore a 24 hour delivery may not be possible Please note these wheels are not suitable for foam filling as standard. Please ask about an upgrade using our Butyl inner tubes to suit this purpose or otherwise consider our puncture proof range of wheels.



| | |
|-------------------------|--|
| Load Capacity (kg) | 350 |
| Wheel Material | Pneumatic tyre on Pressed Steel |
| Diameter (mm) | 400 |
| Bearing Type | Roller |
| Hub Width (mm) | 65 |
| Bore Size (mm) | 20 |
| Tread (mm) | 100 |
| Colour / Shore Hardness | Black Pneumatic Tyre on Steel Rims / 6 Ply |
| Temperature Resistance | -10 °C TO +60 °C |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

