T: 01249 822222
E: sales@bilgroup.co.uk
W: www.bilgroup.co.uk

Pneumatic 400mm Roller Bearing Wheel 350kg Load



Product code: BZWPMR400256D

Black pneumatic tyred grey steel disc centred wheel with a roller bearing bore (sorry no grease nipple). Fitted with a 6 ply diamond tread patterned tyre. Wheel diameter 400mm, tread width 100mm, hub 75mm, bore 25mm. Load capacity 350kg for non-towing applications. REACH Compliant. Please note we manufacture to order and therefore a 24 hour delivery may not be possible. Maximum SWL are quoted according to speed: higher speed will reduce SWL. Load capacities recorded on tyre walls represent manufacturers recommended maximum load at 10 KPH, whilst higher SWL figures stated within our catalogue are based upon 4kph maximum speeds. Refer to our catalogue for SWL if the wheel is never to be used at over 4kph rather than the figure recorded on the tyre. Always check the intended application and base the required SWL capacity according to speed rating. If you have any doubts then please contact BIL before using these wheels. Please note these wheels are not suitable for foam filling as standard. Please ask about an upgrade using our Butyl inner tubes to suit this purpose or otherwise consider our puncture proof range of wheels.

Wheel Material	Pneumatic tyre on Pressed Steel
Diameter (mm)	400
Load Capacity (kg)	350
Bearing Type	Roller
Bore Size (mm)	25
Tread (mm)	100
Hub Width (mm)	75
Colour / Shore Hardness	Black Pneumatic Tyre on Steel Rims / 6 Ply
Temperature Resistance	-10 °C TO +60 °C