



Polyurethane Cast Iron Plate Swivel Castor 100mm 200kg Load

Product code: JAB100PTBJ

Open screw thread jacking castor with side fitting nuts with 160mm lift fitted with a 100mm white zinc plated swivel pressed steel castor with a brown polyurethane tyred cast iron centred wheel with ball bearing with a load capacity of 200kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units.1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in bending the thread but more likely the castor will tear away from the screw thread. Please refer to the BIL catalogue or request a drawing



| Diameter (mm) | 100 |
|--------------------------|--|
| Castor Height (mm) | 128 |
| Castor Type | Swivel |
| Swivel Radius (mm) | 90 |
| Fixing Option | Plate |
| Bearing Type | Ball |
| To Suit Fixing Bolt (mm) | 12 |
| Wheel Material | Polyurethane on Cast Iron |
| Colour / Shore Hardness | Brown Polyurethane on Cast Iron Rim / 94 Shore A |
| Temperature Resistance | -20 °C TO +80 °C |
| Load Capacity (kg) | 200 |
| Tread (mm) | 40 |
| Height (mm) | 438 |
| Lifting Stroke (mm) | 160 |





