

## Polyurethane Cast Iron Plate Swivel Castor 125mm 200kg Load

**Product code: JAB125PTBJ**

Open screw thread jacking castor with side fitting nuts with 160mm lift fitted with a 125mm white zinc plated swivel pressed steel castor with a brown polyurethane tyred cast iron centred wheel with ball bearing bore with a load capacity of 200kg Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. 1 extra safety point is when jacked up please beware of any obstacles as a sudden shock could result in bending the thread but more likely the castor will tear away from the screw thread. Please refer to the BIL catalogue or request a drawing



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 125  |
| Castor Height (mm)       | 156  |
| Castor Type              | Swivel   |
| Swivel Radius (mm)       | 104  |
| Fixing Option            | Plate  |
| Bearing Type             | Ball   |
| To Suit Fixing Bolt (mm) | 12   |
| Wheel Material           | Polyurethane on Cast Iron                        |
| Colour / Shore Hardness  | Brown Polyurethane on Cast Iron Rim / 94 Shore A |
| Temperature Resistance   | -20 °C TO +80 °C                                 |
| Load Capacity (kg)       | 200  |
| Tread (mm)               | 40   |
| Height (mm)              | 466  |
| Lifting Stroke (mm)      | 160  |

## BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

