

Polyurethane Cast Iron Plate Swivel Castor 250mm 2800kg Load

Product code: JAZHD2XL250PTBJ



Side plate fixing fabricated zinc plated jacking unit fitted with a twin wheel 250mm swivel castor with 2 x polyurethane on cast iron centred ball bearing wheels, Tread width 60mm x 2 plate size 200mm x 110mm, hole centres 135mm x 80mm, height 719mm/869mm, maximum lift is 150mm. Load capacity 2800kg. Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. for other dimensions please refer to the BIL catalogue or request a drawing. When jacked up to the height please beware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. DO NOT OVERWIND Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)

Diameter (mm)	250
Castor Height (mm)	314
Castor Type	Swivel
Swivel Radius (mm)	220
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	16
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / 94 Shore A
Temperature Resistance	-20 °C TO +80 °C
Load Capacity (kg)	2800
Tread (mm)	2 x 60
Height (mm)	731 / 881
Lifting Stroke (mm)	150
Handle Option	Fixed

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

